

# 700HA32A234L

Allen-Bradley 700-HA Tube Base Relay 10A 2CO 240VAC Coil with Pushbutton + LED



GENERAL PURPOSE RELAYS



Allen-Bradley



|                |                              |
|----------------|------------------------------|
| Component type | Switching relay              |
| Range          | Panel Mount and Power Relays |
| Model          | N/A                          |
| Product status | Existing                     |

## ELECTRICAL

|                                            |                    |
|--------------------------------------------|--------------------|
| Nominal current                            | 10 A               |
| Nominal voltage AC                         | 250 V              |
| Number of contacts as change-over contact  | 2                  |
| Rated switching power at AC-1              | 2500 VA            |
| Rated switching power at AC-15, 230V       | 500 VA             |
| Breaking capacity at DC-1, 30V             | 10 A               |
| Voltage type for actuating                 | AC                 |
| Control supply voltage Us at AC 50HZ       | 240 V              |
| Control supply voltage Us at AC 60HZ       | 240 V              |
| With LED indication                        | Yes                |
| Type of electric connection                | Plug-in connection |
| Electrical life at Un, In (service cycles) | 100000 cycles      |
| Operating voltage                          | 192-264 V          |

## CONSTRUCTION

|                                      |               |
|--------------------------------------|---------------|
| Material contact                     | Silver nickel |
| With latching test button            | Yes           |
| Suitable for plug-in socket mounting | Yes           |
| IP rating                            | IP40          |

## MECHANICAL

|                                  |                    |
|----------------------------------|--------------------|
| Mechanical life (service cycles) | 2.0E7 cycles       |
| Max. shock acceleration          | 50 g               |
| Max. vibration acceleration      | 5 m/s <sup>2</sup> |

## DIMENSIONS

|        |         |
|--------|---------|
| Width  | 32.8 mm |
| Height | 36.5 mm |
| Depth  | 54.1 mm |

## ENVIRONMENT

|                       |             |
|-----------------------|-------------|
| Operating temperature | -40...70 °C |
|-----------------------|-------------|

# 700HA32A234L

Allen-Bradley 700-HA Tube Base Relay 10A 2CO 240VAC Coil  
with Pushbutton + LED



GENERAL PURPOSE RELAYS



**Allen-Bradley**

## DIMENSIONAL DIAGRAM

