
SSFBS20C4P

Socomec SSF Fuse Switch Kit, with External Handle, suits BS fuses, 4P 20A

BS FUSE HOLDERS AND SWITCHES



Component type	Fuse switch disconnector
Range	Fuse Switch
Model	N/A
Product status	Existing

The Socomec SSF standard fuse switches boast IP 30 protection on all fuse terminals in a compact yet effective design. These fuse switches feature a test position and double-break contacts per phase, allowing the safe isolation of AC or DC circuits as well as the added short circuit protection offered by DIN/BS type HRC fuses.

ELECTRICAL	Rated current	20 A
	Max. rated operation voltage Ue AC	690 V
	Max. rated operation voltage Ue DC	440 V
	Rated permanent current at AC-21, 400 V	20 A
	Rated permanent current at AC-23, 400 V	20 A
	Short time withstand current Icw, 1 sec	80 kA
	Rated impulse withstand voltage Uimp	8 kV
	Rated insulation voltage Ui	750 V
	Rated operation power at AC-23, 400 V	9 kW
CONSTRUCTION	Degree of protection (IP), front side	IP30
MECHANICAL	Suitable for fuses	Other
	Mechanical life (service cycles)	20000 cycles
DIMENSIONS	Height	98 mm
	Width	96 mm
	Depth	83 mm

Published on 21 July 2026