


TAS102BH12501A

IME TAS102 Solid Core Current Transformer Horizontal
1250A/1A 102 x 54mm 20VA Class 1 15VA Class 0.5



CURRENT TRANSFORMERS
AND TRANSDUCERS

IME



Component type	Current transformer
Range	Solid Core CT
Model	N/A
Product status	Existing

The IME solid core current transformers are highly accurate and cover a broad range of sizes and form factors that suit busbar, cable or protection class applications.

ELECTRICAL

Primary rated current	1250 A
Secondary current on CT	1 A
Rated operating frequency	47-63 Hz
Max. operating voltage (Umax)	0.72 V
Rated short time thermal current I _{th} (x primary current)	75 kA
Rated continuous thermal current I _{cth} (x primary current)	75 kA
Accuracy class	0.5
Insulation class (IEC 61869-1, 61869-2)	B
Rated burden, class 0.5	15 VA
Rated burden, class 1	20 VA
Power loss	27 W
Over current limiting factor	FS 5
Secondary rated apparent power	15 VA

CONSTRUCTION

Current transformer type	Solid core
Material housing	Polycarbonate (PC)
Model	Attachable current transformer
With shock protection	Yes
Snap mounting	Yes
Secondary connection	Screw connection

ENVIRONMENT

Number of primary inputs	1
Storage temperature	-40...85 °C

TAS102BH12501A




IME TAS102 Solid Core Current Transformer Horizontal
1250A/1A 102 x 54mm 20VA Class 1 15VA Class 0.5



CURRENT TRANSFORMERS
AND TRANSDUCERS

IME

DIMENSIONAL DIAGRAM



*Opzione/Option

