

100SC23VA404BC

Allen-Bradley 100SC Safety Contactor 11kW 4Pole 230 to 240VAC Coil 4NC Contact Aux Bifurcated



Component type	Power contactor, AC switching
Range	100SC
Model	N/A
Alternative	CALL FOR ALTERNATIVE

The Allen-Bradley Bulletin 100S-C safety contactors provide mechanically linked positively guided or mirror contact performance, required in the feedback circuits of modern safety applications.

ELECTRICAL

Number of normally open contacts as main contact	4
Number of normally closed contacts as main contact	0
Rated operation current Ie at AC-3, 400 V	23 A
Rated operation power at AC-3, 400 V	11 kW
Rated operation current Ie at AC-1, 400 V	32 A
Max. rated operation voltage Ue AC	690 V
Voltage type for actuating	AC
Rated control supply voltage Us at AC 50HZ	230-240 V
Number of auxiliary contacts as normally open contact	0
Number of auxiliary contacts as normally closed contact	4
Rated operation current Ie at AC-3, 690 V	12 A
Rated operation power at AC-3, 690 V	10 kW
Rated operation power at AC-4, 400 V	4 kW
Power consumption, AC coil pickup	75 VA
Power consumption, AC coil hold-in	9.5 VA
Type of electrical connection of main circuit	Screw connection
Rated operation current Ie at AC-4, 400 V	9 A

CONSTRUCTION

IP rating	IP20
Mounting method	DIN-rail/screw

DIMENSIONS

Height	81 mm
Width	45 mm
Depth	119.5 mm
Weight	0.45 kg