

140GH2C3C40

Allen-Bradley 140G MCCB H Frame 36kA 3P 40A Fixed Thermal Magnetic



Component type	Power switching circuit breaker
Range	Moulded Case Circuit Breaker
Model	N/A
Product status	Existing

The Allen Bradley motor protection circuit breakers offer a reliable solution with both short-circuit and overload protection for individual motor loads with high interrupt ratings for 2 and 3 pole devices. Ideal for motor starting and motor protection applications. Connecting modules are available and have been combination short-circuit tested with the Allen Bradley 100-E contactors.

ELECTRICAL

Rated current I_n	40 A
Number of poles	3
Max. rated operation voltage U_e AC	690 V
Rated ultimate short-circuit breaking capacity I_{cu} at 415 V, 50 Hz	36 kA
Rated service short-circuit breaking capacity I_{cs} at 400 V, 50 Hz	36 kA
Type of protection trip unit	Thermal/magnetic release
Trip curve	Fixed thermal, fixed magnetic
Frame size rating	160 A
Rated frequency	50-60 Hz
Rated insulation voltage U_i	1000 V
Suitable for isolation	Yes
Rated short circuit breaking capacity, I_{cu} 690V AC	10 kA
Rated short circuit breaking capacity, I_{cs} 690V AC	10 kA
Rated impulse withstand voltage U_{imp}	8 kV
Reverse connection of supply possible	Yes
Electrical life at U_n, I_n (service cycles)	8000 cycles
Power loss	11.1 W

MECHANICAL

DIN rail (top hat rail) mounting optional	Yes
Mechanical life (service cycles)	25000 cycles

DIMENSIONS

Height	130 mm
Width	90 mm
Pole connection pitch	30 mm
Built-in depth	82.5 mm
Depth (toggle included)	116 mm

140GH2C3C40

Allen-Bradley 140G MCCB H Frame 36kA 3P 40A Fixed Thermal Magnetic



Allen-Bradley

DIMENSIONS	Weight	1.2 kg
ENVIRONMENT	Rated surrounding temperature without derating	40 °C
	Maximum operating temperature	75 °C
	Storage temperature	-40...80 °C
	Max. altitude before derating	2000 m