

140MPA3E40

Allen-Bradley 140MP Motor Protection Circuit Breaker Frame A
2.5 to 4.0A



Component type	Motor protection circuit-breaker
Range	140MP
Model	N/A
Product status	Existing

The Allen-Bradley Bulletin 140MP Motor Protection Circuit Breakers provide magnetic short-circuit and thermal overload protection up to 32 A, with an interrupting rating 400V of up to 100 kA. Available in a range of accessories and tested in combination with Allen-Bradley Bulletin 100-C and 100-K contactors creating two-component motor starters.

ELECTRICAL

Rated permanent current I_u	4 A
Switch off technique	Thermomagnetic
Long time overload protection adjustment range	2.5-4 A
Max. rated operation voltage U_e	690 V
Rated short-circuit breaking capacity I_{cu} at 400 V, AC	75 kA
Rated operation power at AC-3, 400 V	1.5 kW
Type of control element	Turn handle
Type of electrical connection of main circuit	Screw connection
Number of poles	3

CONSTRUCTION

IP rating	IP2X
------------------	------

MECHANICAL

Max. tightening torque	2.5 Nm
-------------------------------	--------

DIMENSIONS

Height	90 mm
Width	45 mm
Depth	85.5 mm
Weight	0.28 kg