140MTD9NC32

Allen-Bradley 140MT Motor Circuit Protector 32A

MOTOR PROTECTION



Component type	Motor protection circuit-breaker
Range	140MT
Model	N/A
Product status	Existing

The Allen-Bradley Bulletin 140MT Motor Protection Circuit Breakers provide magnetic short-circuit and thermal overload protection up to 40A. Assembled starters can be applied without additional branch circuit protection. Motor circuit protectors are applied with a separate overload relay for three-component starters, available in two frame sizes.

ELECTRICAL	**Rated uninterrupted current Iu**	32 A
	Switch off technique	Magnetic
	Max. rated operation voltage Ue	690 V
	Rated short-circuit breaking capacity Icu at 400 V, AC	50 kA
	Rated operation power at AC-3, 400 V	15 kW
	With thermal protection	No
	Type of control element	Turn handle
	Type of electrical connection of main circuit	Screw connection
	Number of poles	3
CONSTRUCTION	**IP rating**	IP2X
MECHANICAL	**Max. tightening torque**	2.5 Nm
DIMENSIONS	**Height**	96.3 mm
	Width	45 mm
	Depth	93.7 mm
	Weight	0.41 kg

Published on 02 October 2026

140MTD9NC32

Allen-Bradley 140MT Motor Circuit Protector 32A

MOTOR PROTECTION

DIMENSIONAL DIAGRAM





Note	Information
1	Undervoltage/shunt trip
2	Auxiliary contact (front mounted)

Note	Information
3	Auxiliary contact (side mounted)
4	Screw mounting adapter

Published on 02 October 2026