

150F625NBA

Allen-Bradley SMC Flex Soft Starter 480V 625A ND3W 230 to 240VAC Control



SOFT STARTERS



Allen-Bradley



Component type	Soft starter
Range	SMC Flex
Model	N/A
Product status	Discontinued

The Allen-Bradley SMC Flex Soft Starters feature integral bypass and flexible communications providing advanced performance, diagnostics, and protection. Available with a current range from 5A to 1250A, modular in design for installation and commissioning, with built-in LCD displays and communication modules ensuring connection to multiple networks.

ELECTRICAL

Rated power three-phase motor, inline, at 400 V	355 kW
Rated power three-phase motor, inside delta, at 400 V	630 kW
Rated operating voltage Ue	200-480 V
Integrated motor overload protection	Yes
Release class	Adjustable
Internal bypass	Yes
Voltage type for actuating	AC
Rated control supply voltage Us at AC 50HZ	230-240 V
Rated control supply voltage Us at AC 60HZ	230-240 V
Function	Single direction

CONSTRUCTION

With display	Yes
IP rating	IP00

DIMENSIONS

Height	1041.1 mm
Width	596.9 mm
Depth	346.2 mm
Weight	179 kg

ENVIRONMENT

Rated surrounding temperature without derating	40 °C
--	-------