

1606XLP36C

Allen-Bradley 1606 Power Supply Compact 1Phase 100 to 240V
AC to Plus Minus 12 to 15V DC 36W 2.8A



POWER SUPPLIES



Allen-Bradley



Component type	DC-power supply
Range	1606
Model	N/A
Product status	Existing

The Allen-Bradley 1606 Switched Mode Power Supplies are the ideal solution for reliable and efficient power supply. Features compact design with wide input voltage range (single and multi phase AC and DC), power boosts, in-built redundancy and conformal coating for harsh environments. Available with multiple output voltage levels and wide power output range to accommodate various load sizes.

ELECTRICAL

Voltage type of supply voltage	AC/DC
Rated supply voltage at AC 50 Hz	100-240 V
Rated supply voltage at DC	85-375 V
Frequency	50-60 Hz
Nominal current (In)	0.4 A
Max. starting current	35 A
1st secondary output voltage	-15-15 V
Max. output current 1	2.5 A
Nominal value output current 1	2.8 A
Nominal value output voltage 1	12 V
Power output	36 W
Power consumption	5.9 VA
Efficiency	86 %
Type of electric connection	Spring clamp connection
With LED indication	Yes
Secondary voltage adjustable	Yes
Rated supply voltage at AC 60 Hz	100-240 V
Output voltage stabilized	Yes

CONSTRUCTION

Rail mounting possible	Yes
Wall mounting possible	Yes
IP rating	IP20
Direct mounting possible	No
Degree of protection (NEMA)	Other

DIMENSIONS

Width	45 mm
Height	75 mm
Depth	91 mm

1606XLP36C

Allen-Bradley 1606 Power Supply Compact 1Phase 100 to 240V
AC to Plus Minus 12 to 15V DC 36W 2.8A



POWER SUPPLIES



Allen-Bradley

DIMENSIONS	Weight	0.24 kg
ENVIRONMENT	Operating temperature	-10...70 °C
	Stabilized	Yes