

1762OV32T

Allen-Bradley MicroLogix Expansion Module 32DO Sink 24VDC



MICRO CONTROL SYSTEMS



Allen-Bradley



Component type	PLC digital I/O-module
Range	MicroLogix
Model	N/A
Product status	Existing

Allen-Bradley MicroLogix™ 1400 programmable logic controllers are ideal for streamlining manufacturing processes. Available with EtherNet/IP™, on-line editing capability, built-in LCD panel, high I/O count, faster high-speed counters, pulse train output, use of RSLogix500 and enhanced network capabilities. A user-friendly and scalable solution for controlling complex processes and machinery.

ELECTRICAL

Type of digital output	Transistor
Permitted voltage at output	10.2-26.4 V
Type of output voltage	DC
Digital inputs configurable	No
Digital outputs configurable	No
Output current	4 A
Short-circuit protection, outputs available	No
Redundancy	No
Type of electric connection	Screw connection
Output current at digital output	0.5 A

CONSTRUCTION

Number of digital outputs	32
Suitable for safety functions	No

DIMENSIONS

Width	40.4 mm
Height	90 mm
Depth	87 mm

ENVIRONMENT

Operating temperature	0...55 °C
Storage temperature	-40...85 °C
Max. ambient humidity (non-condensing)	95 %