
# 1794OV16P

**Allen-Bradley Flex I/O 16-Point Digital Output Protected Sink Module 24V DC**

IN CABINET DISTRIBUTED IO




| | |
|---|---|
| **Component type** | Fieldbus, decentr. periphery - analogue/digital I/O module |
| **Range** | FLEX I/O |
| **Model** | N/A |
| **Product status** | Existing |

The Allen-Bradley FLEX™ I/O system offers a flexible, modular, and cost-effective solution for your industrial automation and control. The space saving design offers rack-based I/O functionality of up to eight modules and provides digital, analogue, HART analogue, and specialty I/O with 4...32 points per module with flexible mounting and wiring options.

| | | |
|---|---|---|
| **ELECTRICAL** | Type of digital output | Transistor |
| | Type of voltage (input voltage) | DC |
| | Type of output voltage | DC |
| | Short-circuit protection, digital outputs available | Yes |
| | Supply voltage DC | 24-24 V |
| **CONSTRUCTION** | Suitable for safety functions | No |
| | Number of digital outputs | 16 |
| **DIMENSIONS** | Width | 94 mm |
| | Height | 45.7 mm |
| | Depth | 53.3 mm |
| **ENVIRONMENT** | Operating temperature | 0…55 °C |
| | Storage temperature | -40…85 °C |
| | Max. ambient humidity (non-condensing) | 95 % |



Published on 06 October 2026