

2711PK6C20A8

Allen-Bradley PanelView Plus 6 600 Model Terminal 6Inch
Colour Keypad RS232 EtherNet AC



HUMAN MACHINE INTERFACE TERMINALS



Allen-Bradley



Component type	Graphic panel
Range	PanelView Plus 7
Model	N/A
Alternative	CALL FOR ALTERNATIVE

The Allen-Bradley PanelView Plus 7 interfaces form a comprehensive portfolio with standard and performance models providing a view into the control system. The use of FactoryTalk View Machine Edition simplifies configuration and strengthens the Integrated Architecture solution. Ideal for applications requiring control and dynamic information display includes Ethernet connectivity.

ELECTRICAL

Supply voltage AC 50 Hz	100-240 V
Voltage type of supply voltage	AC
Number of pixels, horizontal	320
Number of pixels, vertical	240
Type of display	TFT
Touch technology	None
Useful project memory/user memory	73000 kByte
Supply voltage AC 60 Hz	100-240 V

COMMUNICATION

Number of HW-interfaces industrial Ethernet	1
Number of HW-interfaces USB	2
Supporting protocol for Modbus	No
Supporting protocol for Data-Highway	No
Supporting protocol for DeviceNet	No
Supporting protocol for EtherNet/IP	Yes
Number of HW-interfaces RS-232	1
With SW interfaces	Yes
Supporting protocol for TCP/IP	Yes
Supporting protocol for PROFIBUS	No
Supporting protocol for CAN	No
Supporting protocol for INTERBUS	No
Supporting protocol for ASI	No
Supporting protocol for KNX	No
Supporting protocol for SUCONET	No
Supporting protocol for LON	No
Supporting protocol for PROFINET IO	No
Supporting protocol for PROFINET CBA	No

2711PK6C20A8

Allen-Bradley PanelView Plus 6 600 Model Terminal 6Inch
Colour Keypad RS232 EtherNet AC



HUMAN MACHINE INTERFACE TERMINALS



Allen-Bradley

COMMUNICATION

Supporting protocol for SERCOS	No
Supporting protocol for Foundation Fieldbus	No
Supporting protocol for AS-Interface Safety at Work	No
Supporting protocol for DeviceNet Safety	No
Supporting protocol for INTERBUS-Safety	No
Supporting protocol for PROFI-safe	No
Supporting protocol for SafetyBUS p	No
Supporting protocol for other bus systems	No
Radio standard Bluetooth	No
Radio standard Wi-Fi 802.11	No
Radio standard GPRS	No
Radio standard GSM	No
Radio standard UMTS	No
IO link master	No
With message indication	Yes
With message system (incl. buffer and confirmation)	Yes
With recipes	Yes
Number of password levels	2
Number of online languages	20
Additional software components, loadable	No

CONSTRUCTION

Screen diagonal	5.7 inch
With numeric keyboard	No
Degree of protection (IP), front side	IP66
With alpha numeric keyboard	No
Number of function buttons, programmable	10
Process value representation (output) possible	Yes
Process default value (input) possible	Yes
With printer output	Yes
Degree of protection (NEMA), front side	4X
Rail mounting possible	No
Wall mounting/direct mounting	Yes
Suitable for safety functions	No

PHOTOMETRIC

With colour display	Yes
---------------------	-----

DIMENSIONS

Width of the front	266 mm
Height of the front	167 mm
Built-in depth	98 mm

ENVIRONMENT

Operating temperature	0...55 °C
-----------------------	-----------