

RZ7FSL3AU23

Sprecher and Schuh RZ7 Timer Relay Impulse Converter 24 to 48V DC/ 24 to 240VAC Sply 1CO 0.05-1sec



TIME DELAY RELAYS

sprecher+
schuh



Component type	Timer relay
Range	RZ7
Model	N/A
Alternative	CALL FOR ALTERNATIVE

The Sprecher + Schuh range of RZ7-FS and FE electronic timing relays is a reliable, economical and flexible solution for control and timing application processes. Available in single and multi-function timers, with various timing modes and contact outputs, and timing ranges from 0.05s and up to 300 hours. Optional width sizes including 17.5mm and 22.5mm.

Voltage type for actuating	AC/DC
Rated control supply voltage U_s at DC	24-48 V
Rated control supply voltage U_s at AC 60HZ	24-240 V
Rated control supply voltage U_s at AC 50HZ	24-240 V
Number of outputs, delayed, change-over contact	2
Rated operation current I_e at DC-13, 24 V	1 A
Rated operation current I_e at AC-15, 250 V	3 A
Type of electric connection	Screw connection
Function delay-on energization	No
Function delay on de-energization	No
Function floating contact on energization	No
Function floating contact on de-energization	No
Function star-delta	No
Function pulse shaping	No
Function flashing, starting with pause, fixed time	No
Function flashing, starting with pulse, fixed time	No
Clock function, starting with pause, variable	Yes
Clock function, starting with pulse, variable	Yes
Time range	0.05-1 s
Time setting accuracy	5 %
Power supply reset time	50 ms
Electrical lifespan (control contacts)	100000 c (contacts)
Real power	0.5 W
Degree of protection (IP), front side	IP30

ELECTRICAL

CONSTRUCTION

RZ7FSL3AU23

Sprecher and Schuh RZ7 Timer Relay Impulse Converter 24 to 48V DC/ 24 to 240VAC Sply 1CO 0.05-1sec



TIME DELAY RELAYS

sprecher+
schuh

CONSTRUCTION	Degree of protection (IP), rear side	IP20
	Suitable for DIN rail (top hat rail) mounting	Yes
MECHANICAL	Mechanical lifetime (control contacts)	3.0E7 c (contacts)
	Max. shock acceleration	50 g
	Max. vibration acceleration	4 m/s ²
	Height	78.8 mm
DIMENSIONS	Depth	109 mm
	Width	22.5 mm
ENVIRONMENT	Operating temperature	-25...45 °C