


V4AR395

PROCONNECT 3PV4 Appliance Inlet, 3P+E+2p, 250A, suits 95mm² cable, w/ Crimp Terminals



HIGH CURRENT PLUGS



Component type	Round socket/plug for high currents
Range	3PX/3PV
Model	N/A
Product status	Existing

The Proconnect 3PX and 3PV range of high-current plugs and sockets suit a variety of industries including mining, marine, transportation, and commercial. Available in either a screw ring (3PV) or push-pull connection (3PX) type. Current ratings of 160A to 660A (at 3.3 kV) and corrosion-proof aluminium construction make it ideal for the harsh Australian environment.

ELECTRICAL	Amperage	250 A
	Voltage	1-3300 V
	Contact configuration	3P+E+2P
CONSTRUCTION	Construction type	Inlet
	Material insulation body	Other
	Contact material	Other
	Material screw	Stainless steel
	IP rating	IP67
DIMENSIONS	Width	116 mm
	Length	116 mm
	Height	80 mm
	Weight	1.8 kg
ENVIRONMENT	Operating temperature	-30...60 °C

V4AR395



PROCONNECT 3PV4 Appliance Inlet, 3P+E+2p, 250A, suits
95mm² cable, w/ Crimp Terminals



HIGH CURRENT PLUGS



DIMENSIONAL DIAGRAM



RELATED PRODUCTS

ACCESSORY



Item No: 3PV4PC

Required: No

Description: PROCONNECT 3PV4 Appliance
Inlet, Plug Cap