

700HA33Z24

Allen-Bradley 700-HA General Purpose Tube Base Relay 10A 3
Changeover 3PDT 24V DC Coil



GENERAL PURPOSE RELAYS



Allen-Bradley



Component type	Switching relay
Range	Panel Mount and Power Relays
Model	N/A
Product status	Existing

ELECTRICAL

Nominal current	10 A
Nominal voltage AC	250 V
Number of contacts as change-over contact	3
Rated switching power at AC-1	2500 VA
Rated switching power at AC-15, 230V	500 VA
Breaking capacity at DC-1, 30V	10 A
Voltage type for actuating	DC
Control supply voltage Us at DC	24 V
Type of electric connection	Plug-in connection
Electrical life at Un, In (service cycles)	100000 cycles

CONSTRUCTION

Material contact	Silver nickel
Suitable for plug-in socket mounting	Yes
IP rating	IP40

MECHANICAL

Mechanical life (service cycles)	5.0E7 cycles
Max. shock acceleration	50 g
Max. vibration acceleration	5 m/s ²

DIMENSIONS

Width	32.8 mm
Height	36.5 mm
Depth	54.1 mm

ENVIRONMENT

Operating temperature	-40...70 °C
-----------------------	-------------

700HA33Z24

Allen-Bradley 700-HA General Purpose Tube Base Relay 10A 3
Changeover 3PDT 24V DC Coil



GENERAL PURPOSE RELAYS



Allen-Bradley

DIMENSIONAL DIAGRAM

