EEXRCSI561O1S5M

Steute HAE Limit Switch Ex 1,2,21,22 Magnetic Coded Safety Sensor 5m

LIMIT SWITCHES

.steute



Component type	Limit switch
Range	HAE Limit Switch
Model	N/A
Product status	Existing

Steute Technologies offer a wide range of explosion-proof HAE position limit switches for industrial applications, with optional safety functions. Explosion-proof limit switches are offered with thermoplastic or metal enclosures with slow or snap action. Ideal for use in areas with hazardous gas, vapours, mists, hazardous powder, dust or in extreme cold (down to -60°C).

ELECTRICAL	Number of contacts as normally closed contact	1
	Number of contacts as normally open contact	1
	Number of contacts as change-over contact	0
	Type of control element	Other
	Type of electric connection	With cable preassembled
	Rated operation current Ie at AC-15, 230 V	0 A
	Rated operation current Ie at DC-13, 230 V	0 A
	Forced opening	No
COMMUNICATION	Type of interface	None
	Type of interface for safety communication	None
CONSTRUCTION	Material housing	Plastic
	IP rating	IP67
	Construction type housing	Other
	Alignment of the control element	Other
	Suitable for safety functions	Yes
MECHANICAL	Switching function	Other
	Switching function latching	No
DIMENSIONS	Cable length	5 m
	Height of sensor	16 mm
	Length of sensor	50 mm
	Width sensor	40 mm
ENVIRONMENT	Rated temperature	-20…70 °C
CERTIFICATES/APPROVALS	Explosion safety category for gas	Other
	Explosion safety category for dust	Other

Published on 20 October 2026


EEXRCSI561O1S5M

Steute HAE Limit Switch Ex 1,2,21,22 Magnetic Coded Safety Sensor 5m

LIMIT SWITCHES

.steute

DIMENSIONAL DIAGRAM



Published on 20 October 2026