MBP00160A3P

Mersen DIN Panel Mount Fuse Disconnectors 160A suits Size 00





Component type	Fuse switch disconnector
Range	DIN Fuse Disconnect
Model	N/A
Product status	Phased Out

The Mersen DIN Fuse Disconnects are compact and reliable devices that combine switch functionality with high protection level of fuses. They are suitable for IEC low voltage systems and accept various classes of NH power fuses. They are easy to install and operate, with service entrance capability and CE mark.

	Rated current	160 A
ELECTRICAL	Max. rated operation voltage Ue AC	690 V
	Max. rated operation voltage Ue DC	440 V
	Rated impulse withstand voltage Uimp	8 kV
	Rated insulation voltage Ui	1000 V
CONSTRUCTION	Degree of protection (IP), front side	IP30
MECHANICAL	Suitable for fuses	NH00
	Height	202 mm
DIMENSIONS	Width	108 mm
	Depth	81 mm

RELATED PRODUCTS

ACCESSORY Item No: MBBCS003P Item No: MBBCS23P Required: No Required: No TO DE TOUT **Description:** Mersen DIN Busbar Mount Cable **Description:** Mersen DIN Base Mount Cable Lugs Shroud Size 00 Shroud suits Size 2 3Pole Item No: MBBCS13P Item No: MBCC1 Required: No Required: No Description: Mersen DIN Base Mount Cable **Description:** Mersen DIN Wedge Clamp Size Shroud suits Size 1 3Pole 1 Single Each

MBP00160A3P

Mersen DIN Panel Mount Fuse Disconnectors 160A suits Size 00

RELATED PRODUCTS

ACCESSORY

en DIN Pilot Switch Lid and 00 and 2 and 3 Fuse

