RGC1A23D30KKE

Carlo Gavazzi Solid State Relay 30A 24 to 240V AC Switching 3 to 32V DC Screw





| Component type | Solid state relay |
|----------------|-------------------|
| Range | Solid State Relay |
| Model | N/A |
| Product status | Existing |

The Carlo Gavazzi Solid State Relays (SSR) are ideal for a wide range of applications including AC and DC switching, 1-phase and 3-phase and temperature control. With fast switching capability, they are the most reliable switching components for process accuracy. A wide range of accessories available such as heatsinks, terminal adaptors, protection covers, communication and thermal interfaces.

| ELECTRICAL | Rated current In | 30 A |
|--------------|---|----------|
| | Rated control supply voltage Us at AC 50HZ | 0-0 V |
| | Rated control supply voltage Us at AC 60HZ | 0-0 V |
| | Rated control supply voltage Us at DC | 3-32 V |
| | Voltage type for actuating | DC |
| | Operating voltage | 24-264 V |
| | Number of contacts as normally open contact | 1 |
| | Rated operation current le at AC-1 | 0 A |
| | Rated operation current le at AC-3 | 0 A |
| | Rated operation current le at AC-51 | 30 A |
| | Rated operation current le at AC-53a | 8 A |
| | Rated operation current le at AC-53b | 0 A |
| | Switching at zero-crossing | Yes |
| | Number of phases | 1 |
| CONSTRUCTION | Degree of protection (IP) | IP20 |
| | Modular version | Yes |
| DIMENSIONS | Height | 110 mm |
| | Width | 22.5 mm |
| | Depth | 140.5 mm |
| | Weight | 0.38 kg |

RGC1A23D30KKE

Carlo Gavazzi Solid State Relay 30A 24 to 240V AC Switching 3 to 32V DC Screw



DIMENSIONAL DIAGRAM





