

V4CE435

PROCONNECT 3PV4 Extension Socket, 3P+N+E+2P 16, suits 0A 35m cable, w/ Crimp Terminals




HIGH CURRENT PLUGS



Component type	Round socket/plug for high currents
Range	3PX/3PV
Model	N/A
Product status	Existing

The Proconnect 3PX and 3PV range of high-current plugs and sockets suit a variety of industries including mining, marine, transportation, and commercial. Available in either a screw ring (3PV) or push-pull connection (3PX) type. Current ratings of 160A to 660A (at 3.3 kV) and corrosion-proof aluminium construction make it ideal for the harsh Australian environment.



ELECTRICAL	Amperage	160 A
	Voltage	1-3300 V
	Contact configuration	3P+N+E+2P
CONSTRUCTION	Construction type	Coupling
	Material insulation body	Other
	Contact material	Other
	Material screw	Stainless steel
	IP rating	IP67
DIMENSIONS	Width	130 mm
	Length	303 mm
	Weight	2.7 kg
ENVIRONMENT	Operating temperature	-30...60 °C

V4CE435


PROCONNECT 3PV4 Extension Socket, 3P+N+E+2p,2P 16,
suits0A 35m cable, w/ Crimp Terminals



HIGH CURRENT PLUGS



DIMENSIONAL DIAGRAM



RELATED PRODUCTS

ACCESSORY



Item No: 3PV4PC

Required: No

Description: PROCONNECT 3PV4 Appliance
Inlet, Plug Cap